

Braided Flexible Sprinkler Hose "NEWAGEFLEX"



BRAIDED FLEXIBLE HOSE

MODEL	NI27SB-700	NI27SB-1000	NI27SB-1200	NI27SB-1500	NI27SB-1800
LENGTH (in MM)	700	1000	1200	1500	1800
Max.Working Pressure	200 PSI	200 PSI	200 PSI	200 PSI	200 PSI
Inlet Nipple	1" BSPT	1" BSPT	1" BSPT	1" BSPT	1" BSPT
Outlet Reducer	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT
Material of Construction	SS 304	SS 304	SS 304	SS 304	SS 304
SUITABLE K-FACTOR	5.6 & 8	5.6 & 8	5.6 & 8	5.6 & 8	5.6 & 8
Approval	UL Listed & FM Approved				
MODEL	NI28SB-700	NI28SB-1000	NI28B-1200	NI28SB-1500	NI28SB-1800
LENGTH (in MM)	700	1000	1200	1500	1800
Max.Working Pressure	200 PSI	200 PSI	200 PSI	200 PSI	200 PSI
Inlet Nipple	1" BSPT	1" BSPT	1" BSPT	1" BSPT	1" BSPT
Outlet Reducer	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT	1/2"NPT OR 3/4"NPT
Material of Construction	SS 304	SS 304	SS 304	SS 304	SS 304
SUITABLE K-FACTOR	5.6 & 8	5.6 & 8	5.6 & 8	5.6 & 8	5.6 & 8
Approval	UL Listed & FM Approved				