

Monitors

Water Foam Monitor : Torpedo



I Monitor with Nozzle



- Wide range 500GPM, 750GPM, 1000GPM, 2000GPM, 4000 GPM
- Anti corrosive Stainless steel construction
- Excellent compatibility with AFFF foam
- Fog angle up to 120°
- 3% foam-proportioning nozzle
- Designed for working pressure up to 10 kg/cm²

Product Code No.	Nozzle	Flow@100PSI (7kg/cm ²)		Foam Induction
		GPM	LPM	
A-FM-500	AFN-500	500	1890	3%
A-FM-750	AFN-750	750	2840	3%
A-FM-1000	AFN-1000	1000	3785	3%
A-FM-2000	AFN-2000	2000	7570	3%
A-FM-4000	AFN-4000	4000	15100	3%
A-FM-8000	AFN-8000	5000	30200	3%

II Jet Ratio Controller Pump (JRCP)



- Compatible to use with UL listed water & foam monitor (TORPEDO)
- Corrosion resistant, excellent compatibility with AFFF foam
- With pressure gauges
- Covered in S.S casing for easy handling and storage
- With pick up tube and strainer

Product Code No.	Nozzle Flow at 100 PSI		JRCP Flow at 100 PSI		Foam Solutions Induction
	GPM	LPM	LPM	GPM	
JRCP-1000	1000	3785	125	33	3%
JRCP-2000	2000	7570	190	50	3%
JRCP-4000	4000	15100	450	120	3%
JRCP-8000	8000	30200	900	240	3%